

Data sheet
SM 022 (022-1BD00)
Technical data

| | |
|---------------------------------|----------------------------|
| Order no. | 022-1BD00 |
| Type | SM 022 |
| Module ID | 0104 AFA0 |
| General information | |
| Note | - |
| Features | 4x DO DC 24 V 0,5 A |
| PWM data | |
| PWM channels | - |
| PWM time basis | - |
| Period length | - |
| Minimum pulse width | - |
| Type of output | - |
| Safety | |
| Safety protocol | - |
| Safety requirements | - |
| Secure user address | - |
| Watchdog | - |
| Two channels | - |
| Test pulse length | - |
| Circuit monitoring | - |
| Datasizes | |
| Input bytes | 0 |
| Output bytes | 1 |
| Parameter bytes | 0 |
| Diagnostic bytes | 0 |
| Housing | |
| Material | PPE / PPE GF10 |
| Mounting | Profile rail 35 mm |
| Mechanical data | |
| Dimensions (WxHxD) | 12.9 mm x 109 mm x 76.5 mm |
| Net weight | 57 g |
| Weight including accessories | 57 g |
| Gross weight | 71 g |
| Environmental conditions | |
| Operating temperature | 0 °C to 60 °C |
| Storage temperature | -25 °C to 70 °C |
| Certifications | |
| UL certification | yes |
| KC certification | yes |