



thanos

TOUCH ROOM OPERATING UNIT





thanos L white



thanos S black



thanos LQ white

Simplicity can be that smart «

thanos

The top-end of our room operating units is now gaining a new brother – the multi-functional “thanos”. Being a design-oriented and flexible addition to our portfolio, it provides new features and possibilities in room controls.

All settings and options are visualized in a 3,5” TFT display covered by scratch-resistant glass. The user gets an immediate visual and optical response whenever he changes any parameters.

Even though thanos uses features of most common applications in building automation, users and integrators can still individualize functions and screen. Typical parameters such as temperature setpoint, fan control, blinds/shutters and light control can be adjusted by touching the glass surface.

ADVANTAGES.

- » Adjustment and parameterization of common HVAC features with touch technology
- » Compatible with the EasySens® product line based on EnOcean ISO/IEC 14543-3-10
- » Seamless integration into common BUS systems
- » High quality material for design-oriented interior design
- » Free configurable buttons (28 buttons for thanos S, 12 buttons for thanos L)
- » Customized – instead of date and time individual colour graphics can be shown (e.g. company logo or hotel name; not available for LON and KNX)

TECHNICAL HIGHLIGHTS.

- » Integrated temperature detection, relative humidity optional
- » Bidirectional communication to the EnOcean system and devices
- » Compatible with digitalSTROM, KNX, LON or Modbus
- » Capacitive touch glass surface for intuitive control
- » High resolution 3,5” TFT graphic display
- » Brushed aluminium function clip
- » Available types: L, S, LQ, SQ
- » Power supply 24 V or 100..240 V

EasySens®
The self-powered, intelligent Sensor System

enocean®

KNX®

digitalSTROM

LONMARK®

Modbus

» Discover thanos online!
www.thermokon.de/en/product-highlights/thanos.html





Individual colour graphics can be shown (e.g. company logo or hotel name)*

Integrated temperature detection (humidity optional)

ECO note* (several steps, red to green)

Brushed aluminium function clip

Individually configurable function buttons, individual labelling

Capacitive touch glass surface

thanos SR Wireless

The high-end touch room operating unit supports the EnOcean standard ISO/IEC 14543-3-10, which enables a wireless bidirectional communication to further EnOcean devices.

Besides typical room parameters such as temperature, relative humidity and fan stage also occupancy, date/time and window statuses can be displayed.

Hotels and companies can also have their logo displayed as a screensaver or permanently to label their customized central room unit. Different channels can be configured for dedicated heating/cooling districts as well as de-/humidifying.

The brushed aluminium clip is equipped with a touch sensor and can be parameterized for multiple functions e.g. Master ON/OFF.

The room operating unit uses a bidirectional EnOcean interface for wireless communication, which can be configured using our free airConfig software for remote commissioning.

- » Bidirectional communication thanks to an integrated EnOcean communication interface.
- » Comfortable remote commissioning with airConfig
- » Individual configuration of up to 12 capacitive touch buttons (thanos L version)
- » Easy integration into existing BUS systems



*not possible with LON and KNX



thanos rH S dS

Living smart: acting as a central unit for the digitalSTROM concept, thanos rH S dS can establish up to 8 different functional groups.

It supports all functional groups of the digitalSTROM architecture such as Lighting, Blinds/shutters, Heating/Cooling, Audio, Video, Occupancy and App buttons.

In addition to three main screens for central control functions, the thanos can be set up for up to 8 sub-menus of before mentioned functional groups.

It can also act as an occupancy interface to shut down or power defined functional groups such as lighting or audio. Additional information on alarm, panic or fire as well as weather forecasts can be integrated and send push notifications to your mobile.

- » Smart operating unit for complete and central room control (colours black or white)
- » Integrated sensors for detection of room temperature and relative humidity
- » Individual designation of 3 main screens for central operation of up to 8 sub menus for dedicated functions
- » Possibility of audio-visual indication of events such as alarm, panic, fire

- » Displaying of current weather such as wind, hail or rain via icons
- » Communication is using the existing 230 V power network, no additional BUS wires will be required to enable a local communication
- » Plug and play via the digitalSTROM configurator or via smart phone or system app
- » Easy mounting on the wall in combination with a standard flush-mounted installation box



Multiple menus for different applications and scenes





HOME OF SENSOR TECHNOLOGY



CONTACT

Thermokon Sensortechnik GmbH

Platanenweg 1 | 35756 Mittenaar | Germany
Phone: +49 2778 6960-0 | Fax: +49 2778 6960-400
email@thermokon.de | www.thermokon.de

AUSTRIA

Thermokon Components GmbH

Heid-Werkstraße 4 | 2000 Stockerau
Phone: +43 2266 67485 | Fax: +43 2266 67485-34
info@thermokon.at | www.thermokon.at

CHINA

Thermokon Automation Equipment Co. Ltd.

479 Chun Dong Road | Xin Zhuang Industry Park,
Building C-1, 2/Floor | 201108 Shanghai
Phone: +86 21 5176 0211 | Fax: +86 21 5176 0213
info@thermokon.asia | www.thermokon.asia

FINLAND

Thermokon Sensor Technology Finland OY

Edelfeltinkatu | 48200 Kotka
Phone: +358 40 5525 442
info@thermokon.fi | www.thermokon.fi

HONG KONG

Thermokon Sensor Technology Ltd.

Flat 6, 21/F, Lucida Industrial Building
43, Wang Lung Street | Tsuen Wan | Hong Kong
Phone: +852 3628 3760 | Fax: +852 3628 3762
info@thermokon.asia | www.thermokon.asia

NETHERLANDS

Thermokon Sensor Technology Nederland B.V.

Rozenstraat 11 | 6361 HS Nuth
Phone: +3165 05 50 61 99
email@thermokon.nl | www.thermokon.nl

SWEDEN

Thermokon-Danelko Elektronik AB

Metallgatan 1b | 26272 Ängelholm
Phone: +46 4 3144 84 54 | Fax: +46 4 3114 19 0
info@thermokon.se | www.thermokon.se

SWITZERLAND

Thermokon Sensortechnik Schweiz AG

Zürichstraße 46 | 8303 Bassersdorf
Phone: +41 447 5250-00 | Fax: +41 447 5250-01
email@thermokon.ch | www.thermokon.ch

USA

Thermokon Americas LP

FOR DETAILS PLEASE SEE:
www.thermokon.de/en/contact/
international-locations.html

NORWAY

Thermokon Norge AS

FOR DETAILS PLEASE SEE:
www.thermokon.de/en/contact/
international-locations.html